



Volatile Organic Compound Emissions from Cargo Systems on Oil Tankers

(First edition 2019, updated 2026)



Issued by the

Oil Companies International Marine Forum

29 Queen Anne's Gate
London SW1H 9BU
United Kingdom
Telephone: +44 (0)20 7654 1200
Email: enquiries@ocimf.org

www.ocimf.org

First edition 2019, updated 2026

© Oil Companies International Marine Forum

The Oil Companies International Marine Forum (OCIMF)

Founded in 1970, the Oil Companies International Marine Forum (OCIMF) is a voluntary association of oil companies having an interest in the shipment and terminalling of crude oil, oil products, petrochemicals and gas, and includes companies engaged in offshore marine operations supporting oil and gas exploration, development and production.

Our vision is a global marine industry that causes no harm to people or the environment.

Our mission is to lead the global marine industry in the promotion of safe and environmentally responsible transportation of crude oil, oil products, petrochemicals and gas, and to drive the same values in the management of related offshore marine operations. We do this by developing best practices in the design, construction and safe operation of tankers, barges and offshore vessels and their interfaces with terminals and considering human factors in everything we do.

Terms of Use

While the advice given in this briefing paper ("Paper") has been developed using the best information currently available, it is intended purely as guidance to be used at the user's own risk. No responsibility is accepted by the Oil Companies International Marine Forum ("OCIMF"), the membership of OCIMF or by any person, firm, corporation or organisation (who or which has been in any way concerned with the furnishing of information or data, the compilation or any translation, publishing, supply or sale of the Paper) for the accuracy of any information or advice given in the Paper or any omission from the Paper or for any consequence whatsoever resulting directly or indirectly from compliance with, or adoption of or reliance on guidance contained in the Paper even if caused by a failure to exercise reasonable care.

The content of this publication must never be entered, whether in whole or in part, into any artificial intelligence (AI) system (such as ChatGPT, Co-Pilot, Watson, etc) at any time.

This publication whether in whole or in part may not be utilized in any manner whatsoever, whether directly or indirectly, to train, or develop artificial intelligence (AI) systems, machine learning models, or any other automated technologies. In accordance with Article 4(3) of the Digital Single Market Directive 2019/790, OCIMF expressly reserves this work from the text and data mining exception.

Contents

Glossary	5
Abbreviations	6
Bibliography	7
1 Introduction	8
2 Regulations	8
3 Volatile Organic Compound generating mechanisms	9
4 Environmental impact of Volatile Organic Compound emissions	9
5 Light end product losses: minimising Volatile Organic Compound emissions	10
6 Volatile Organic Compound emission control methods, systems and procedures	10
6.1 Reduced volatility	10
6.2 Vapour balancing	10
6.3 Thermal oxidation	10
6.4 Absorption	10
6.5 Adsorption	11
6.6 Membrane separation	11
6.7 Condensation	11
6.8 Cargo Pipeline Partial Pressure Control	11
6.9 Sequential Transfer of Tank Atmosphere	11
6.10 Maintaining cargo tank pressure	12
6.11 Increased cargo tank atmosphere pressure	12
7 Operational procedures and Volatile Organic Compound Management Plan	12
8 Ship to facility interface	13
9 Performance expectations	13
10 Measurement and verification of Volatile Organic Compound system effectiveness	13
11 Safety concerns	14

12	Training	14
13	Considerations	14
13.1	Design and installation	14
13.2	Redundancy of systems and equipment	15
13.3	Electrical loads	15
13.4	Materials	15

Glossary

Absorption A physical or chemical phenomenon or a process in which atoms, molecules or ions enter some bulk phase – gas, liquid or solid material.

Adsorption The adhesion of atoms, molecules or ions from a gas, liquid or dissolved solid to a surface.

Carcinogenic Any substance that is an agent directly involved in causing cancer.

Catalytic oxidisers Oxidation systems that control Volatile Organic Compound (VOC) and volatile emissions.

Energy recovery Method in which a part or all the waste material produced in a process is burned to generate heat or electricity.

Evaporation Vaporisation of a liquid that occurs from the surface of a liquid into a gaseous phase that is not saturated with the evaporating substance.

Flashing When crude is exposed to temperature increases or pressure decreases during transfer and VOCs are released.

Fractionate A separation process in which a certain quantity of a mixture (gas, liquid, solid, enzymes, suspension or isotope) is divided during a phase transition into a number of smaller quantities (fractions) in which the composition varies according to a gradient.

Inert gas A gas that does not undergo chemical reactions under a set of given conditions.

Light end products More volatile products that are the result of the refining process, pure components that are separated out from crude oil.

Recommendations OCIMF supports and endorses a particular method of working or procedure.

Teratogenic Any agent that can disturb the development of an embryo or foetus.

Toxic A substance that is poisonous to a living organism.

Vaporisation A phase transition from the liquid phase to vapour.

Vapour balancing The transfer of vapour displaced by incoming cargo from the receiving tank of a vessel to the tank of a facility/offshore unit delivering the cargo.

Vapour Emission Control System (VECS) An arrangement of piping and equipment used to control vapour emissions collected in a tank. Includes the vapour collection system and vapour processing unit.

Vapour pressure The pressure produced by a vapour in contact with its liquid or solid form at a given temperature in a closed container.

Vapour saturation Vapour at the temperature of the boiling point corresponding to its pressure and so incapable of being compressed or cooled without condensing.

VOCON procedure A procedure that requires the monitoring and the recording of the pressure drop during a release of gas from the cargo tank vapour system.

VOCON research project A project sponsored by private enterprises and government agencies to advance the competence in the petroleum transportation industry for the development of a cost-effective solution for reduction in VOC emissions from crude storage and tanker transport.

VOCON valve A vapour pressure release control valve used to monitor pressure drops during vapour releases limiting VOC emissions.

Volatile Organic Compound (VOC) Any organic compound having an initial boiling point less than or equal to 250°C (482°F) measured at a standard atmospheric pressure of 101.3kPa.

Volatility A condition of a substance that is capable of being evaporated or changed to a vapour at a relatively low temperature.

Abbreviations

CO₂	Carbon Dioxide
IAPP	International Air Pollution Prevention
IMO	International Maritime Organization
IPCC	Intergovernmental Panel on Climate Change
KVOC	Knutsen VOC Technology
MARPOL	The International Convention for the Prevention of Pollution from Ships
MEPC	Marine Environment Protection Committee
NMVO	Non-Methane Volatile Organic Compound
NO_x	Nitrogen Oxides
P/V	Pressure/Vacuum
Sm³	Standard Cubic Metre
SO_x	Sulphur Oxides
STTA	Sequential Transfer of Tank Atmosphere
VECS	Vapour Emission Control System
VOC	Volatile Organic Compound
VOCON	Volatile Organic Compound Control

Bibliography

CO₂, CH₄, and N₂O Emissions from Transportation-Water-Borne Navigation. In Background papers: IPCC Expert Meetings on Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories (Intergovernmental Panel on Climate Change (IPCC))

MEPC.185(59) Guidelines for the Development of a Volatile Organic Compound (VOC) Management Plan for Tankers Carrying Crude Oil (IMO)

MEPC.1/Circ.680 Technical Information on Systems and Operation to Assist Development of VOC Management Plans (IMO)

VOC Management for International Shipping – Proposed Volatile Organic Compounds Control Measures under MARPOL Annex VI (DNV – study submitted to IMO ISWG-GHG 9 by Canada and Norway)

1 Introduction

Volatile Organic Compounds (VOCs) are any organic compounds that have an initial boiling point less than or equal to 250°C (482°F) when measured at a standard atmospheric pressure of 101.3kPa. VOCs are a mixture of light end hydrocarbons (such as methane, ethane, propane or butane) that evaporate within the range of normal atmospheric conditions. VOCs are generated when cargo flashes in the piping system from the source to the cargo tanks, and from evaporation from the oil surface inside the cargo oil tanks during and after loading. During loading of crude oil tankers and the subsequent vessel transit, VOCs may be released to the atmosphere together with the inert gas.

The cargo tank atmosphere initially contains nitrogen, Carbon Dioxide (CO₂), other non-methane compounds, and traces of VOCs from previous cargo. During loading, hydrocarbon gases (methane–pentane and heavier components) are also released from the cargo. The release of these compounds, combined with the rising cargo level, results in a pressure increase of the cargo tank that is eventually vented to the atmosphere. The reasons for reducing VOC emissions are twofold: environmental protection and to minimise light end product losses.

This information paper presents the technologies and methods that may be available for controlling or treating VOC emissions from oil tanker loading and during vessel transit. Choice of technologies and level of complexity may depend on their application and be context specific.

This information paper has been updated in 2026 to reflect current regulations (section 2), current practice (section 6), performance (section 9) and training (section 12).

2 Regulations

The International Maritime Organization has published technical information on system and operation guidelines to assist in the development of VOC Management Plans in MEPC.1/Circ.680 (27 July 2009), which is a supplement to resolution MEPC.185(59) that came into effect on 1 July 2010. The IMO requires all member states to develop a VOC Management Plan that follows Marine Environment Protection Committee (MEPC) guidelines. The circular states: “The purpose of the VOC management plan is to ensure that the operation of a tanker, to which regulation 15 of MARPOL Annex VI applies, prevents or minimises VOC emissions to the extent possible.”

Vapour Emission Control System (VECS) MSC/Circ.585 (16 April 1992) – MARPOL Annex VI/15 are the standards that have been developed for the design, construction and operation of vapour collection systems on tankers. In addition to these requirements, each tanker that has a vapour processing unit onboard should meet the vapour collection and processing design requirements for a shoreside terminal, to the satisfaction of the country/Flag State of the ship’s registry. While there is a requirement for a VOC Management Plan, there is no requirement for a VECS.

Because of heightened local regulations, Norway has produced a number of technologies for controlling the escape of VOCs. On 1 January 2012, the Norwegian Environment Agency imposed an upper limit for emissions of 0.45kg Non-Methane VOC (NMVOC)/Sm³ crude oil per loading point as a mean value measured over one calendar year. This requirement will be met if the mean emissions from all fields on the Norwegian continental shelf do not exceed 0.45kg NMVOC/Sm³ crude oil loaded during a calendar year.

3 Volatile Organic Compound generating mechanisms

VOCs in cargo tanks are caused by a build-up of positive pressure that occurs during loading, the loaded voyage to the discharge port and transit from discharge to the next load port.

During the loading of oil tankers, the inert gas tank atmosphere (which is infused with residual VOC) has to be displaced. It can be displaced to the atmosphere, to an onboard VOC control method or to an onshore VOC processing unit (via a VECS connection) to allow the cargo to fill the tank while keeping the tank's atmosphere below the Pressure/Vacuum (P/V) valve pressure setting. For tankers this venting is normally done using a vent mast riser system.

During the loading process or in the transit stages, the amount of VOCs that have evolved into the inert gas tank atmosphere is linked to the oil's volatility. Volatility is the tendency of a substance to vaporise.

VOC emissions are created through vaporisation, evaporation and boiling. These processes can be manipulated to control VOC production in the tank atmosphere and capture VOCs in any fitted processing equipment before it is vented into the atmosphere.

Vaporisation is the process of phase transformation between solid or liquid to the gaseous phase. The main vaporisation processes that drive the production of VOCs are evaporation and boiling.

Evaporation is a type of vaporisation from a liquid's surface into a gaseous phase that is not saturated with the evaporating substance. Factors that affect evaporation and therefore the VOC content of a tank's vapour space are temperature, pressure, concentration of substance evaporating in the vapour space, concentration of other substances in the vapour space, flow rate of vapour in the vapour space, density and surface area.

Boiling is the rapid vaporisation of a liquid, which occurs when a liquid is heated to its boiling point, i.e. the temperature at which the vapour pressure of the liquid is equal to the pressure exerted on the liquid by the surrounding atmosphere.

4 Environmental impact of Volatile Organic Compound emissions

There are two types of VOCs: methane and non-methane (NMVOC). The lightest components (mainly methane) contribute to the greenhouse effect. The heavier components (NMVOC) contribute to low-level petrochemical oxidants, such as ozone, which may be detrimental to human health, food production and the environment. In addition, some VOC emissions from light end products are classified as toxic, carcinogenic and teratogenic.

During tanker loading operations, there is a higher flow of inert gas/VOC emissions exiting the cargo tanks through the mast riser into the atmosphere. The high flow rate can result in higher than normal VOC generation and can trap oil in the inert gas/VOC flow, which can then spill on the vessel deck.

5 Light end product losses: minimising Volatile Organic Compound emissions

Light end product losses resulting from VOC emissions also mean a loss of cargo if the light end products are not captured, processed and incorporated back into the cargo tanks. Dictated by local, regional or international requirements, vessel owners/operators have been testing and finding economic and efficient means to recover VOC emissions. The proper use of vapour emission control systems and the associated technologies helps to reduce these cargo losses.

6 Volatile Organic Compound emission control methods, systems and procedures

There are two generic approaches to VOC recovery, known as active and passive VOC recovery technology. Active VOC emission systems typically include a compression step followed by condensation, absorption and/or adsorption. Passive VOC systems use vapour-balanced loading/unloading with VOC as blanket gas.

This section lists the VOC emission control methods, systems, procedures and associated technologies that may be available for treating or limiting VOC emissions from oil tankers while loading and during vessel transit.

6.1 Reduced volatility

Cargo volatility can be reduced by removing the volatile components of the crude oil from the tank of the facility or offshore platform before it is loaded onto the vessel. However, in most cases this is not feasible due to the use of equipment that is found in the petroleum refining process and associated safety considerations, and therefore it is not considered a viable option.

6.2 Vapour balancing

Vapour is displaced by incoming cargo from an oil tanker's receiving tank back to the offloading tank at the terminal or on the offshore facility delivering the crude oil. This vapour balancing method is not practical because the difference in temperature between the offloading and receiving tank can lead to a mismatch in volumes of vapour, vapour contaminants may be incompatible and the methods for collecting vapour in the tanks may be different.

6.3 Thermal oxidation

Thermal oxidation (via thermal combustion) is a method of controlling VOC emissions. VOC-laden air is combusted using enclosed flares to catalytic oxidisers with heat recovery. Risks to consider include safety and combustion emissions (CO₂, Nitrogen Oxides (NO_x), Sulphur Oxides (SO_x), etc.). These risks can be mitigated by using flame/detonation arrestors, inerting, enrichment or dilution, and by following management procedures.

6.4 Absorption

Absorption by chilled or cryogenic liquid is another method to reduce VOC emissions. The chilled liquid absorbent is fed concurrent to the flow of the hydrocarbon vapours through a packed column. The hydrocarbon vapours dissolve in the absorbent and are removed from the air/vapour mixture.

6.5 Adsorption

Adsorption is the process where an air/vapour/gas mixture passes through a bed of activated carbon. Organic molecules are adsorbed on to the carbon and permanent gases such as air or CO₂ pass through the carbon bed and are vented to the atmosphere. If the activated carbon becomes saturated (the breakthrough point), no more molecules can adsorb and vapours will pass through. In order to maintain uninterrupted operation, two activated carbon beds with automatic switching between the two is recommended. The standby activated carbon bed is then regenerated while the active carbon bed is in use. Regeneration of the adsorbent is usually accomplished by stream stripping or by vacuum. Depending on the carbon bed sizes, the nature of the adsorbent material used and the degree of regeneration, this method can reach up to 99% efficiency.

6.6 Membrane separation

The membrane separation technique uses a liquid compressor and a semi-permeable membrane to separate organic molecules from air/vapour mixtures, with the membrane more permeable to organic compounds than to inorganic gases. The air/vapour mixture passes over one side of the membrane. Organic molecules selectively migrate through the membrane, are removed by a vacuum pump and are returned to the inlet side of the compressor.

6.7 Condensation

Chilled or cryogenic condensation involves passing the vented gas/vapour through compressor stages and suitable condensers using cooling media such as sea water, glycol, propylene or liquid nitrogen. This lowers the temperature of the gas/vapour, resulting in lowering of VOC concentrations that exit the condensers, then drains into a collection tank, from which it can be recycled, reclaimed or recovered for reuse. This method can reach about 80% to 99% efficiency, depending on coolant media. Any surplus emissions may be handled using thermal oxidation (see section 6.3), typically by using a steam boiler or gas turbine.

6.8 Cargo Pipeline Partial Pressure Control

Cargo Pipeline Partial Pressure Control technology (such as KVOC or equivalent) is designed to prevent changes in properties by pressure-balancing the crude oil transfer and preventing VOC emissions from being generated. This technology does not use any power and there is no production of harmful combustion emissions, such as CO₂ and NO_x. Using a large diameter drop pipe with increased pressure inside reduces the evaporation of the VOCs generated through pressure differentials created within the drop lines when loading cargo. This arrangement may reduce pressure build-up, and therefore VOC generation in the cargo.

6.9 Sequential Transfer of Tank Atmosphere

The Sequential Transfer of Tank Atmosphere (STTA) is an operational procedure that moves cargo tank atmosphere (VOC and inert gas) sequentially between the cargo tanks before venting to the atmosphere. The movement of cargo tank atmosphere is caused by displacement of the gases during the loading of cargo. This procedure requires installation of a special gas piping arrangement from cargo tank to cargo tank. The tanks also need to be separated into several groups so that the cargo tank atmosphere follows a complex route through a series of tanks before it is emitted from the hull into the atmosphere. The piping arrangement should be designed so that it can be opened and closed at different points to account for different loading programmes. This process avoids excessive venting of VOC gases, for a portion of the loading cycle, by prioritising venting of clean inert gases from empty tanks over the higher VOC atmosphere of the tank being loaded.

6.10 Maintaining cargo tank pressure

Maintaining cargo tank pressure (such as VOCON or equivalent) is a method of limiting manual release to a tank pressure that is close to the true vapour pressure of the cargo, instead of a much lower pressure. The method requires both constant pressure valves and an automated release valve. This procedure allows tank pressures of the cargo tanks to be maintained at a higher mean level with smaller, more accurate automated tank venting releases. Maintaining the cargo tank pressure at standard P/V valve settings of 0.14 bar on laden transit could reduce VOC emissions by approximately 30% compared to manual release.

6.11 Increased cargo tank atmosphere pressure

Raising the P/V valve settings (including other associated system components such as P/V breakers) from the standard 0.14 bar to 0.2 bar, while maintaining a high tank pressure (as noted in section 6.10), could enhance the reduction of VOC emissions during laden transit from 30% to around 40%, all within the current structural integrity limits of the cargo tanks.

If the P/V valve settings are increased further to 0.6 bar, the reduction in VOC emissions during laden transit could reach approximately 80%, although this would require the cargo tanks to be constructed for a higher design pressure. Additionally, VOC emissions during offshore loading with shuttle tankers have been lowered by up to 40% when operating at 0.6 bar settings (see *VOC Management for International Shipping – Proposed Volatile Organic Compounds Control Measures under MARPOL Annex VI* for further details).

7 Operational procedures and Volatile Organic Compound Management Plan

The purpose of the VOC Management Plan is to ensure that tanker operations, to which regulation 15 of MARPOL Annex VI Reg.15.6 applies, prevent or minimise VOC emissions as much as possible. VOC emissions generated during loading and transit should be evaluated and operational procedures developed to ensure the best management practices for preventing/minimising their emission. This includes design changes, devices/equipment and operational procedures to manage VOC emissions, such as cargo tank operating procedures, crude oil washing, tank venting, tank operating pressures and adding of inert gas, all with the intent of preventing the release of gas emissions.

The VOC Management Plan, as required by MARPOL Annex VI Reg.15.6, must be approved by the vessel's Flag State or recognised organisation before obtaining an International Air Pollution Prevention (IAPP) Certificate. Model plans are provided by Flag States and recognised organisations that may be used by the ship operators as guidance when developing a fleet's plan.

The plan should be oil tanker-specific and include data related to:

- The VECS manual.
- The vapour recovery system manual.
- Any other VOC control system manuals.
- The inert gas system manual.
- The crude oil washing manual.
- Operation of P/V valves.

As well as the system manuals, the following drawings should also be included in the plan:

- General arrangement.
- Capacity plan.
- Cargo tank venting system piping diagram.
- Inert gas system piping diagram.
- VECS piping diagram.
- Vapour recovery system or other VOC control system drawings.

The plan should state the designated person responsible for implementing the VOC Management Plan and its associated procedures onboard the vessel. It should also allow the delegation of specific tasks and duties to other personnel. Duties and responsibilities of the designated person should be clearly defined within the plan and that designated person should conform to the VOC Management Plan requirements.

8 Ship to facility interface

The interface between ship and shore, ship and production (floating and fixed) or ship and storage (floating and fixed) facilities is based on the configuration of the overall system layouts and specific shore and production field situation.

If an oil tanker is loaded from a fixed production and storage platform or floating facility through a loading buoy or submerged turret, the VOC emission control methods and associated systems are installed on the oil tanker, if applicable.

If an oil tanker is loaded from a shore facility, a floating production or a floating storage unit, VOCs are recovered using a fixed piping arrangement (onshore) or a floating hose arrangement (offshore) from the oil tanker to a VOC recovery plant installed at the shore facility, or on the floating production unit if the VOC processing equipment is installed. These arrangements are designed based on the specific requirements and, if installed, can effectively manage VOC emissions.

9 Performance expectations

The performance/recovery rates of the different emission control methods and VOC control systems vary, depending on the method and system.

Some of the systems noted in this paper are better suited for transit VOC recovery than for loading and their performance and recovery rates will differ accordingly. Currently, two of the systems best suited for vessel transiting are the backpressure control and maintaining cargo tank pressure.

10 Measurement and verification of Volatile Organic Compound system effectiveness

MARPOL Annex VI/15 is the requirement for operating a vapour collection system on tankers. A VOC Management Plan, developed by the ship operator, is the means used to measure and verify VOC system effectiveness.

Record keeping is essential for documenting performance. The form of record keeping depends on the method used to minimise VOC emission from the crude oil cargo. Recording the time and pressure before and after a release is required. This information should be compiled by the ship operator to assess and quantify the extent or degree of VOC release.

11 Safety concerns

Since there are several types of VOC control methods and systems on the market, and since cargoes are diverse, performing a robust risk assessment with the manufacturer is recommended. The risk assessment should encompass all the conditions that the installed VOC control methods and systems will be certified to operate under, based on all the potential safety hazards. The risk assessment should include the specific cargo operations the vessel may undergo, including fail safe conditions. The risk assessment should also determine personnel training requirements (see section 12).

12 Training

Personnel responsible for overseeing the VOC arrangement onboard the vessel must complete a training programme that has been developed for the purpose and included in the VOC Management Plan.

This training programme should cover:

- The purpose of VOC emission control.
- Overview of the regulations.
- Principles of emission control (including VOC generation systems and tanker pressure control/release systems).
- General methods and systems for the control of VOC emissions.
- Guidance on overall testing systems and maintenance.
- Understanding principles for ship-to-ship transfers.
- Vessel-specific methods and systems and their control.
- Methods of monitoring and recording.
- Hazards and safety issues related to VOC emission control.

13 Considerations

13.1 Design and installation

VOC emission control systems are designed to create an arrangement that will meet the following objectives:

- Best suited for the vessel's trade route, loading terminal and discharge facility.
- Meets the regulatory requirements.
- Operates efficiently.

The design and installation challenges of the VOC emission control systems will depend on whether passive or active systems or a combination of the two are used. Space restriction may be a factor and additional power requirements will be needed to operate more sophisticated active systems. Design and installation are best considered for new building projects as they allow more flexibility in system selection and installation. Retrofitting of existing vessels is limited to the systems that require higher tank pressure or increased power consumption to operate effectively.

13.2 Redundancy of systems and equipment

There are no established operating procedures or regulations to ensure system and equipment redundancy and performance standards. However, Classification Societies and Flag State rules and regulations include requirements for specific equipment, redundant safety systems, testing of safety systems and training. The system and equipment redundancy should be risk assessed and based on the equipment being considered, the type of system that is best suited and its overall design and functional requirements.

13.3 Electrical loads

The power requirements, as well as the complexity of the process equipment, are somewhat higher for active systems (reliquification, adsorption and absorption) than passive systems. However, passive systems may not maximise VOC emission removal. A combined arrangement of the two technologies can maximise VOC emission removal while minimising the power required and the energy consumed. This should be evaluated on a case-by-case basis.

13.4 Materials

Each VOC emission control system is unique. Depending on its arrangement it may require special materials based on the temperature and corrosiveness of VOC emissions. The materials will be subject to the manufacturer's design and the Classification Society's and Flag State's rules and regulations.



Our vision

A global marine industry that causes no harm to people or the environment

**Oil Companies
International Marine Forum**
29 Queen Anne's Gate
London SW1H 9BU
United Kingdom

T +44 (0)20 7654 1200
E enquiries@ocimf.org

ocimf.org